

# PAINTED NUBBY™

Square Lay-in & Tegular  
medium texture



Painted Nubby™ panels with Prelude® XL® 15/16" suspension system (Pgs. 458-459)

This panel offers excellent acoustical absorption with a medium-textured fabric visual.

## KEY SELECTION ATTRIBUTES


- Outstanding acoustical performance; both Articulation Class (180-190) and NRC (0.85-0.95)
- Fiberglass substrate resists mold and mildew
- 30-Year Limited System Warranty against visible sag, mold, and mildew

## COLOR



White  
(WH)

## DETAILS



1. Painted Nubby™ Tegular
2. Painted Nubby™ Tegular with Silhouette® 9/16" suspension system 1/4" reveal

# PAINTED NUBBY™

## Square Lay-in & Tegular medium texture

UP TO **71%** RECYCLED CONTENT

Calculate LEED contribution at [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

LEED® energy management construction waste to mgmt regional materials design for flexibility EPD recyclable/extended producer resp. bio-based materials recycled content sourcing of raw materials material ingredient reporting low emitting materials lighting quality acoustics





### VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 474-478 <a href="http://armstrongceilings.com/catdwgs">armstrongceilings.com/catdwgs</a>	Item No.	Dimensions (Inches)
--------------	--	----------	---------------------

#### PAINTED NUBBY™ Square Lay-in

15/16" Square Lay-in 	1	<b>3102</b>	24 x 24 x 1" 
	1	<b>3101</b>	24 x 48 x 3/4" 
	1	<b>3103</b>	24 x 48 x 1" 
	1	<b>3104</b>	48 x 96 x 1" 

#### PAINTED NUBBY Tegular

15/16" Square Tegular 	8	<b>3200</b>	24 x 24 x 1" 
9/16" Square Tegular 	26, 43, 47, 51, 55	<b>3201</b>	24 x 24 x 1" 

#### Size Capabilities

	Width	Length
15/16" or 9/16" Square Tegular	<b>Made-to-Order Sizes (3-4 Wks)</b>	<b>3/4" or 1" Thick</b> 4" - 48"      4" - 120"

<sup>1</sup>Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.


### PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics		Total Acoustics <sup>1</sup>		Articulation Class	Fire Performance	Light Reflect	Mold & Mildew Protection	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
NRC	+	CAC	=	AC	Class	Light	Bio-Block	Humi-Guard+					
0.95	N/A	-	190	Class A	0.84	•	•	-	Std	•	-	•	
0.85	N/A	-	180	Class A	0.84	•	•	-	Std	•	-	•	
0.95	N/A	-	190	Class A	0.84	•	•	-	Std	•	-	•	
0.95	N/A	-	190	Class A	0.84	•	•	-	Std	•	-	•	
0.95	N/A	-	190	Class A	0.84	•	•	-	Std	•	-	•	
0.95	N/A	-	190	Class A	0.84	•	•	-	Std	•	-	•	

### SUSPENSION SYSTEMS



### PHYSICAL DATA

**Material**  
Fiberglass with fabric facing

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled.)

**ASTM E1264 Classification**  
Type XII, Form 2, Pattern E  
Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Mold/Mildew Protection**  
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Acoustical Details**  
A CAC value of 37 can be achieved by backloading fiberglass products with Item 769 or 770.

**Insulation Value**  
3101 - R Factor - 3.0 (BTU units)  
R Factor - 0.53 (Watts units)  
3102, 3103, 3104, 3200, 3201 - R Factor - 4.0 (BTU units)  
R Factor - 0.70 (Watts units)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at [armstrongceilings.com](http://armstrongceilings.com)

**Weight; Square Feet/Carton**  
3101 - 0.44 lbs/SF; 128 SF/ctn  
3102, 3103 - 0.46 lbs/SF; 96 SF/ctn  
3104 - 0.46 lbs/SF; 128 SF/ctn  
3200, 3201 - 0.46 lbs/SF; 48 SF/ctn

**Minimum Order Quantity**  
1 carton, excludes made-to-order panels

**Metric Items Available**  
3102M, 3101M, 3103M, 3200M, 3201M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.